

General Description:

CATALYST # 031 is a poly – functional aromatic isocyanate mix with suitable solvent for a fast and flexible hardener for polyurethane sealer.

Major Uses:

To be mix with polyurethane sealer that requires fast drying, flexible and good sandability on sealer.

Characteristics and Physical Properties:

Appearance	Clear
Solid content	30%
Specific Gravity	0.96
Viscosity FC # 4 @20 ⁰ C	12 + / - 1 sec.
Flash Point	20 ⁰ C

Storage:

Shelf life of 6 months in close container. Always keep to room temperature and keep away from direct sunlight.

Packing:

Available in ½ lit, ½ Usg, and 10 lit.

Physiological Hazards:

CATALYST # 031 does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. The mixture, in its liquid state is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL : 06 – 5311777, FAX 06 - 5311330:

Website : <http://www.maspaints.com> Email : masuae@emirates.net.ae

