



# MASCRAK

## General Description:

MASCRAK is a transparent specialty material developed as a cracking media for water based interior decorative paint. It is formulated as an intermediate coat for Stucco Cracked Finish.

## Characteristics and Physical Properties:

Colour	Transparent
Specific Gravity	1.00 kg/li
Flash Point	>60°C
Viscosity	40" FC # 4 @ 25°C
Solid Content	6%

## Method of Application:

- The surface to be designed with Stucco Cracked Finish should be undercoated with MAS Masonry Primer and MAS PVA Wallfiller to smoothen the surface.
- To a well – prepared surface, apply one coat Mascryl (any choice of colour) as an intermediate coat and let it dry.
- Apply uniformly MASCRAK in a single coat process to obtain smaller crack effect.
- To obtain bigger crack, apply one more coat of MASCRAK on the dried first coat and let it dry.
- Apply normally the Emulsion topcoat of any desired colour that will compliment the colour of the intermediate coat.

- For Stucco Cracked Effect, apply the desired colour of STUCCO by trowel and follow the normal application system of MAS Stucco and keep the material to crack by itself. Final scraping by stainless steel trowel to attain the glossy effect of stucco.

## Dilution:

It is not recommended to dilute the material due to its readiness to use. However, if the material is too thick to apply dilute with demineralised water not more than 5%.

## Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

## Physiological Hazards:

MASCRAK does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. They are not flammable but harmful if swallowed, if contact with eyes occurs, cleanse with fresh water and seek immediate medical advice.

## Precautions:



See Safety Indication

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

