

## General Description:

SILVER PAINT is a brilliant, super resistant copper solution based on 100% acrylic resin with selected silver powder. It is fast drying with exceptional long lasting effect.

## Major Uses:

High recommended for all decorative works on wood, metal, plaster, concrete, precast, old paint and false ceiling.

## Characteristics and Physical Properties:

Colour	Silver
Specific Gravity	0.98 kg/L
Solid Content	30%
Coverage	25 – 28 m <sup>2</sup> / lit.
Flash point	20°C
Dry	12 hrs.
Recoatable	12 hrs.

## Application Details:

Method of application	By brush, Roller or Spray
Dilution	Not required
Mixing Ratio	Single pack

## Surface Preparation:

### Steel:

Substrate must be sandblasted to Sa2 1/2 . If sandblasting is not possible, wire blasting is recommended. The surface should be cleaned, free from dust, oil, grease and other contaminants.

### Concrete:

Surface should be primed with adequate primer, sanded and free from foreign matters.

### Wood:

Substrate should be primed with suitable primer prior to the application of SILVER PAINT.

## Storage:

SILVER PAINT should be kept in cool area below 25°C. Keep tightly closed container

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner as soon as possible.

## Packing:

Available in 1Usg, 1 lit, ½ lit and 250 ml.

## Physiological Hazards:

SILVER PAINT does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. SILVER PAINT is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

