



UVIPRIME # 1000

General Description:

UVIPRIME # 1100 is a mono component UV pigmented radiation curable basecoat based on epoxy acrylic oligomer and reactive monomer. It provides fast curing; good sanding ability, excellent adhesion and high build film coat. It has a very good chemical and mechanical property.

Major Uses:

It is best recommended to be used as basecoat for high quality wooden furniture, plywood, flooring panels, etc.

Characteristics and Physical Properties:

Appearance	White
Specific weight	1.25 g/L
Viscosity	90" (FC # 8 @ 25°C)
Solid content	99%
Flash point	>60°C
Coating rate	40-60 g/m ²
Curing Speed	10-12 m/min. 2 lamps: irradiation Distance : 15 cm. 1 lamp Hg + 1 lamp Ga.
Application condition:	
Air temperature	5°C min
Relative humidity	85% max
Application method	Reverse roller
Sandability	Immediately after UV

Surface Preparation:

- ❖ Substrate should be free from contaminant such as oil and dust, etc.
- ❖ Moisture content of timber should be kept below 15 percent.
- ❖ UVIPRIME # 1100 has to be cured by two(2) lamps (Ga + Hg).

Storage:

Store in the dark, cool and dry places under normal temperature and humidity. Shelf life of 3-4 months at 30°C room temperature.

Packing:

Available in 20 lit. .

Precautions:

UVIPRIME # 1100 contains no solvents, nevertheless use protective gloves and eye goggles when handling this product. It is recommended to provide proper ventilation on working area. If contact with skin or splash in eyes, wash with fresh water and seek medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

