

General Description:

AQUAWOOD FILLER is based on acrylic dispersion resin and selected filler, it is developed to patch – up uneven surface of the wood and to fill nail heads, and cracks.

Major Uses:

AQUAWOOD FILLER is intended to fill cracks, knot holes and all blemishes of natural and synthetic wood. It is recommended for interior and exterior application.

Characteristics and Physical Properties:

Appearance	Paste
Specific weight	1.5
Odour	Characteristic
Solid content (w)	75%
VOC	250 g/l
Colours	Natural Teak Mahogany Oak Dark oak Walnut Ebony

Method of Application:

- The surface must be sanded and should be clean and free from any contaminants.
- Fill the holes and cracks by scraper or putty knife evenly.
- If the material is dry, add a little water to get required consistency.
- AQUAWOOD FILLER should be sanded and stained with appropriate dye or stain prior to the application of NC, PU or Acrylic topcoats.

Storage:

AQUAWOOD FILLER should be kept in a cool area below 25⁰C. Keep in tightly closed container.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 500 ml., 1 lit, 4 lit.

Physiological Hazards:

AQUAWOOD FILLER does not contain dangerous solvents, nevertheless, good ventilation in working area is recommended as well as the use of safety tools and equipment. AQUAWOOD FILLER is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

