



AQUAWOOD PRESERVATIVE

General Description:

AQUAWOOD PRESERVATIVE is a clear/pigmented waterborne preservative for impregnating new and weathered wood. It provides deep penetrations on wood to protect against fungus, blue stains and surface moulds.

Major Uses:

Ideal for use in fencing, gates, portable- out buildings, joinery, door, window frames, cladding in gardens, as well as roof timbers, hard wood and floorboards.

Characteristics and Physical Properties:

Colour	Clear and Pigmented
Specific weight	1.0 kg/L
Viscosity	12" (Ford Cup # 4)
Solid content	32%
Spreading rate	6-8 m ² /L (softwood) 12-14 m ² /L (hardwood)
VOC	48 g/L

Application Details:

Method of Application	Brush or spray
Mixing ratio	Single pack
Thinner	Water

Surface Preparation:

- Surface must be clean, dry, and free from dirt, oil, grease and other foreign matters. If detergent is used for cleaning, rinse with fresh water.
- The temperature of the substrate should be min 5⁰ C, above the dew point. Avoid painting on direct sunlight.

Drying Time:

Touch dry	1-2 hrs.
Hard dry	5 hrs
Recoat	24 hrs.

Storage and Handling:

The product should be kept in accordance with national regulations. AQUAWOOD PRESERVATIVE should be kept in cool place below 25⁰C. Shelf life of 36 months minimum in a tightly closed container. Handle with care, stir well before use.

Cleaning of Tools:

All tools should be cleaned with warm, soapy water as soon as possible.

Packing:

Available in 1lit, Usg and 20 lit Pail,

Physiological Hazards:

AQUAWOOD PRESERVATIVE does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. AQUAWOOD PRESERVATIVE is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advice.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

