



# DAWNWAX

## General Description:

DAWNWAX is an oil based wax that enhances gloss finishes and acts as a sealer for both lime, acrylic based products and surface treatment for wooden substrates. It is made from a blend of special waxes and natural oils, taking the best characteristics of each and blending them to make a superior quality liquid wax.

## Major Uses:

DAWNWAX can be applied to almost any surface where a gloss finish is required and is particularly suitable as a finish coat for all MAS Stucco Venetian plasters. DAWNWAX is waterproof with high performance that provides ultimate protection, while its liquid state allows the addition of pigmented paste, metallic powders and other compatible fine art materials with ease.

## Characteristics and Physical Properties:

Appearance	White liquid
Sp. Gravity	1.0 kg/li.
Flash Point	100 <sup>0</sup> C.
Solid by Weight	40%
Viscosity	paste
Coverage	20-24 m <sup>2</sup> / lit.
Dilution	ready to use
Dying time	
Touch dry	1-3 hours
Buff	12 hours

## Method of Application:

DAWNWAX should be applied with a sponge, rag or spatula/wide putty knife in thin, even coats over an entire surface. It should be allowed to dry up to 3-4 hours before being buffed to a high sheen using a clean rag or mechanical buffer. Ensure good ventilation during application of the product. Keep material in a cool place below 25<sup>0</sup>C. Keep the container tightly closed. Shelf life of 12 months minimum.

## Cleaning of Tools:

All tools should be cleaned with warmth water with soap.

## Packing:

Available in 1 kg, 1 gallon

## Hazards:

DAWNWAX does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. The mixture, in its liquid state is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek immediate medical advice.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

