



E.P. THINNER # 135

General Description:

E.P. THINNER # 135 is a clear, colorless liquid. It is a combination of alcohols, and aromatic hydrocarbon.

Major Uses:

E.P. THINNER # 135 is recommended as a solvent for epoxy paints.

Characteristics and Physical Properties:

Specific Gravity	ASTM D 3505	0.86 Kg. / lit.
Color (Saybolt)	ASTM D 1209	+30
Initial Boiling Point	ASTM D 850	124
Copper Corrosion	ASTM D 849	none
Non – Aromatics	ASTM D 2360	max 60%
Flash Point (Abel)	IP 170	12°C

Packing:

Available in 1USG, 18 lit (Pail) and 200 lit (Drum)

Physiological Hazards:

Avoid contact with skin, eyes and clothing. Do not breathe vapour. Extinguish any naked flames. E. P. THINNER # 135 is flammable and harmful if swallowed. If contact with eyes occurs, cleanse with fresh water and seek immediate medical advise.

Storage:

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition; do not smoke in storage areas.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

