



# FLATWALL ENAMEL

## General Description:

FLATWALL ENAMEL is a finished coat based on synthetic resins, used as flat finish in alkyd systems.

## Advantages:

- Interior surfaces.
- Ease of application
- Good colour retention
- Good hiding power.

## Characteristics and Physical Properties:

Colour	As per RAL colour card
Coverage	10 – 12 m <sup>2</sup> / lit.
Flash Point	39°C
Solid Content	Approx 50% by volume
Recommended	35 microns per coat.

## Drying Time:

Touch Dry	After 2 hrs.
Over coating	min. 12 hrs.
Shelf Life	One (1) year

## Application procedure:

- Substrate must be free from oil and other contaminants.
- If necessary to use undercoat primer as a build and adhesion coat.

## Storage:

FLATWALL ENAMEL should be kept in a cool area below 25°C. Keep in tightly closed container.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or Thinner # 155 as soon as possible.

## Packing:

Available in USG, 5USG and 200 lit. (Drum)

## Physiological Hazards:

FLATWALL ENAMEL does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. FLATWALL ENAMEL is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

