



# HAMMERTONE

## General Description:

HAMMERTONE is based on styrene modified alkyd resin and special synthetic additives and pigments.

## Major Uses:

A special effect HAMMERTONE on steel structures, machineries, outdoor furniture and appliances. This hammertone enamel provides fast drying and good hold out properties.

## Advantages:

- Enhances the beauty of surfaces and provides excellent outlook.
- Prolongs the life span of steel.
- Compatible to oil – based primers.

## Characteristics and Physical Properties:

Color	6 basic colors
Gloss	Semigloss
Flash point	23°C
Volume solids	35% +/- 2
Specific gravity	1.00-1.05
Coverage	12-14 m <sup>2</sup> /L
DFT	23-27 microns

## Application Details:

Method of Application	Spray, brush or roller
Conventional Spray	
Nozzle Orifice	1.4-2.0 mm
Nozzle Pressure	40-55 psi
Thinner / Dilution	Thinner # 255
Application	Temperature of the substrate should be minimum 5°C

## Surface Preparation:

### New Steel / Shop Primed:

Abrasive blasting to minimum Sa 2 ½. If sandblasting is not possible, power tool cleaning or wire brushing is recommended to minor touch – up. All damaged primers and contamination should be removed and thoroughly cleaned prior to final painting.

Apply quick drying primer before application of HAMMERTONE

### Maintenance:

Remove oil, grease and other contaminants prior to final top coating.

### Drying Time:

The drying time is evaluated according to ASTM D 1640 at room temperature. However, the drying time varies on the film thickness, number of coats and temperature.

Dry hard	25-30 min.
Dry to touch	10-15 min.
Dry to recoat	30 min.

## Typical Recommended System:

Quick Drying Primer	1 coat
Hammertone	1 coat

## Storage:

HAMMERTONE should be kept in cool place below 25°C. Keep in tightly closed container.

## Cleaning of Tools:

All tools should be cleaned with Wash Thinner or QD Thinner # 255 as soon as possible.

## Packing:

Available in 1 Usg, 20lit Pail, and 200lit Drum.

## Precautions:

HAMMERTONE ENAMEL does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. HAMMERTONE ENAMEL is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

