

General Description:

Leather Effect is based on a stained nitrocellulose lacquer with selected pigments. It is designed to provide a natural effect of brown leather. The effect may vary from small to big crack depending on the density of the applied material.

Application Procedure:

- Surface must primer by either polyurethane or polyester primer clear.
- Sanding is required before the application of dyed brown and let it dry for about 5 – 10 minutes.
- Apply 1 – 2 coats of NC Gloss # 031 Clear on MDF or NC Gloss RAL 8002 and keep it for a few minutes prior to application of crackled trans, (Leather Tinted).
- Apply 1 – 2 coats of NC Matt clear # 032 or NC Acrylic finish.

Note: *Leather Effect can be obtained as per catalogue with M.D.F. Wood.*

Storage:

Store in cool areas below 25°C. Shelf life is 12 months in closed container. Keep container tightly close.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:

Available in 1Usg.and 20 lit Pail.

Physiological Hazards:

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY : P.O. BOX NO: 23085,SAJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL : 06 – 5311777, FAX 06 - 5311330:

SHOWROOM : P.O. BOX NO: 23085,INDUSTRIAL AREA, SHARJAH, U.A.E

TEL : 06 – 5328533, FAX 06 - 5328610

Website : <http://www.maspaints.com/> Email : masuae@emirates.net.ae

