



MAS LINOL

General Description:

MAS LINOL is a water base and transpiring decorative paint with particular and beautiful satined, antique and classic effect. Easy application helps to redecorate houses, villas, shops, flats etc...

Major Uses:

Best applied for interior and exterior walls, PVC, Steel and Wood.

General Characteristics and Physical Properties:

Appearance	White paint
Specific Weight	0.800 – 1.00 kg. / lit.
Dilution	Ready to use
Coverage	8 – 10 m ² /liter
Drying Time	3 – 4 hrs. at 20°C
VOC	37 g/L
Resistance	Good resistance for abrasion once hardened
Washability	Good after hardened using water and normal detergent
Stability	Approximately one year min. into the packaging.

Application Procedure:

Please ensure that the surface is properly prepared by application of MAS Acrylic Masonry Primer, MAS PVA Wall Filler and Mascryl (any choices of colours as an intermediate coat prior to the application of MAS LINOL. It is imperative to ensure that the surface to be coated should be free from other contaminants, oil, grease and concrete laitance.

Classic Effect:

Apply the paint using the special brush in oblique direction from the top to bottom, alternating the strokes from right to left, in the same direction, wait 10 – 15 minutes until the smooth parts is dried, rough is still wet. Smooth the surface with the special spatola following the used direction. After 4 – 5 hours apply another coat with the same technique following the same direction, with another direction you can obtain another effect.

Antique effect:

Follow the classic method going in horizontal or vertical direction one coat only obtaining beautiful effect. This product is so malleable satisfying your creativity.

Packaging:

Normally 4 kg, and 20 kg in plastic bucket are available upon request.

Colour Availability:

- White base
- Premeasured colorant to get required colours.

Physiological Hazards:

MAS LINOL is water-based paint, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS LINOL is harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

