



# MAS FINETEX RT

## General Description:

A high quality textured finish based on a special acrylic resin with selected aggregates filler creating a decorative finish on the surface. The product enables a thick coating to be created, capable of providing classic style decoration and protecting the surface against alkaline aggressiveness without cracking due to its flexible properties.

## Major Uses:

For interior and exterior decoration on surface made up with mortar of cement, plain concrete, reinforced concrete and on any cement-based plaster in general.

It can be top coated with our range of decorative finishes.

## Characteristics and Physical Properties:

Colour	White
Gloss	Matt
Specific Gravity	1.6 + / - 0.1
pH	8-9
Viscosity	250 poise
Solid content	77% by weight
Coverage	2-4 sq.mt. / lit.
Touch Dry	2-3 hrs.
Dry to recoat	24 hrs.
Shelf Life	12 months
VOC Content	50 grams/liter
Application	By spatula, trowel, marine sponge, decorative roller.
Thinning / cleaning	Water.

## Surface Preparation:

### New Substrates:

- Substrate must be dry and free from any form of contaminants.

- Application of 1 coat of MAS Masonry Primer White to reach an optimal hiding prior to the application of MAS FINETEX RT

### Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer and application of MAS Masonry Primer White for an optimal hiding.

## Application:

Air temperature: min. + 5°C / max. +35°C.

Relative humidity of the air : < 80%

-Avoid applying the product when there is condensation on the surface, or in direct sunlight.

-Product is ready to use, if dilution is required, max. 5% of potable water.

## Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

## Cleaning of Tools:

All Tools should be cleaned with water.

## Packing:

Available in 1Usg. and 5 Usg. Pail

## Precautions:



See Safety Indication Sheet.

*The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.*

## MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: [masuae@emirates.net.ae](mailto:masuae@emirates.net.ae)

