



MAS INTERIOR EMULSION

General Description:

PVA based decorative wall paint that gives matt smooth finish. It is washable, alkali resistant, perfectly formulated for interior walls.

Advantages:

- For interior use.
- Good adhesion properties.
- Good scrub resistance.
- Good drying properties.
- Ease of application.
- Excellent resistance to dirt pick up.
- Non – toxic and environment friendly.

Characteristics and Physical Properties:

Colour	As per colour card
Gloss	Matt
Specific weight	1.35 kg/L
Solid content	35% (by volume)
Coverage	8~8.5 m ² /L
Touch dry	1-2 hrs.
Recoat	5-6 hrs.
Shelf life	12 months
Flash point	>65°C
Application	By brush, roller and airless spray gun

Surface Preparation:

New Substrates:

- Substrate must be free from any form of contaminants.
- Apply 1 – 2 coats of Mas Masonry AR Primer and Mas Masonry Primer White into the substrate.
- Application of Mas PVA Wall filler to smoothen the surface.

- Application of 1 – 2 coats of MAS INTERIOR EMULSION for final coatings.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of masonry primer and PVA wall filler for uneven surfaces prior to application of MAS INTERIOR EMULSION.

Method of Application:

SPETTER COAT	
Recommended thinner	Sweet water
Volume of thinner	Approx. 0 – 5%
Nozzle orifice	4.0 – 6.0 mm
ROLLER	
Recommended thinner	Sweet water
Volume of thinner	Approx. 0 – 5%

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Precautions:



See Safety Indication Sheet

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

