



MAS MASONRY PRIMER

The substrate must be dry, free from dirt, grease, powder, laitance or other contaminations.

General Description:

MAS MASONRY PRIMER is a vinyl acrylic copolymer based under coat. It has good flow and good penetration on different surfaces.

Major Uses:

For use on interior surfaces, like plaster, stucco filler, gypsum boards, concrete and asbestos cement sheeting. It is a new generation of coating that gives unmatched and long lasting maintenance free protection for all buildings. It combines both elasticity and breathing properties.

Characteristics and Physical Properties:

Colour	White
% Solid(v)	34
Specific weight	1.45 g/L
Flash point	>65°C
Coverage	8 – 10 m ² /L
Touch dry	60 min.
Recoat	2-3 hours
Overcoating interval	
minimum	12 hrs
maximum	No limitations

Application Method:

Method of Application	By brush, roller or airless spray
Dilution	Max. 5% water
Airless Spray Data	
Pressure	140-190 kg/cm ²
Nozzle tip	0.021" – 0.027"
Spray angle	65° - 80°

System Specification:

- Impregnation primer to seal and reduce the porosity of the surface, to avoid uneven absorption and provide good adhesion for subsequent coating.
- Suitable for interior application to plaster, brickwork, concrete, and rendered surface.
- Use as primer coat in an emulsion or textured wall coating system.

Recommended System:

MAS Masonry AR Primer	1 coat
MAS Masonry Primer	1 coat
MAS PVA Wallfiller	2 coats
Mascryl	2 coats
MAS Textured Paints	1 coat

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Physiological Hazards:



See Safety Indication Sheet

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E
TEL NO: 009716 5311777; FAX: 009716 5311330
Website : <http://www.mas-paints.com>
Email: masuae@emirates.net.ae

