

General Description:

MAS PROTECT WB is a transparent specialty acrylic- based material formulated as protection for water –based interior and exterior decorative paint.

Major Uses:

For use as a protective coating for special decorative paint to avoid fading and lime efflorescent. Wall transpiration is on the basis of DIN rule 52615 (detaching and support – sticking resistance DIN ISO 4624).

Characteristics and Physical Properties:

Color	Transparent
Specific Gravity	1.0 +/- 0.1
Flash Point	60° C
Viscosity (SP#4-60RPM)	13 Poises.
% Solid Content	28 +/- 0.2

Application Details:

Method of application	By brush , Roller
Mixing Ratio	Ready to use or with 10% water

Surface Preparation:

- Surface must be clean, dry, free from dirt, oil, grease and other foreign matters. If detergent is used for cleaning, rinse with fresh water.
- The temperature of the substrate should be min 5° C, above the dew point. Avoid painting on direct sunlight.
- Apply MAS PROTECT WB by brush or roller.

Drying Time:

On the Surface @25°C	5 hrs.
Overpainting @ 25°C	8 hrs.
Below the Surface @ 25°C	12 hrs

Recommended System:

Decorative Paint	1 coat.
MAS PROTECT WB	2 coats

Storage and Handling:

The product should be kept in accordance with national regulations. MAS PROTECT WB should be kept in cool place below 25°C. Shelf life of 12 months minimum in a tightly closed container. Handle with care, stir well before use.

Cleaning of Tools:

All tools should be cleaned with water

Packing:

Available in 5KG , 25 KG.,

Physiological Hazards:

MAS PROTECT WB does not contain solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. MAS PROTECT WB is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

FACTORY :P.O. BOX NO: 23085,SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL : 06 – 5311777,

FAX 06 - 5311330:

Website

: <http://www.maspaints.com>

Email : masuae@emirates.net.ae

