



MASTIC ROYAL

General Description:

MASTIC ROYAL (ANTIBAC) is acrylic copolymer based emulsion paint with outstanding wash ability and durability. It has good flow that gives a smooth finish and contains anti bacterial and anti fungal component.

Major Uses:

For use on interior surfaces, like plaster, gypsum boards, concrete and asbestos cement sheeting. MASTIC ROYAL (ANTIBAC) is highly recommended for hospitals and public places, due to its active ingredients which exhibits extremely low water solubility and ensures long lasting protection against mildew and fungus. The active ingredients meet the requirements of the XIVth and XXXVIth recommendations of the German Board of Health.

Characteristics and Physical Properties:

Colour	As per RAL & NCS
Appearance	Matt /Eggshell/Silk Semigloss/Gloss
Volume solids	39 %
Specific Gravity	1.2 – 1.5 kg/L
Coverage	8 ~ 10 m ² /L
Drying time @ 25°C	25 min.
Application	Brush / Roller / Spray
VOC	76 g/L

Surface Preparation:

New Substrates:

- Substrate must be free from any form of contaminants.
- Apply 1 coat of MAS Masonry AR Primer as impregnating sealer.

- Apply 1 – 2 coats of MAS Masonry Primer into the substrate.
- Application of MAS PVA Wall filler to smoothen the surface.
- Application of 1 – 2 coats of MASTIC ROYAL (ANTIBAC) for final coatings.

Old Concrete (previously painted)

- Remove all blistered, cracked and peeled off paint from the surface.
- Penetrated paint must be cleared and treated with 3% ammonia and water.
- Glossy finish coat must be sanded.
- Apply 1 coat of Masonry AR Primer, MAS Masonry Primer and PVA Wall filler for uneven surfaces prior to application of MASTIC ROYAL (ANTI BAC)

Recommended System:

MAS Masonry AR Primer	1 Coat.
MAS Masonry Primer White	1 Coat.
PVA Wall Filler	2 Coats.
MASTIC ROYAL (ANTIBAC)	2 Coats.

Storage:

The product must be stored in accordance with national regulations. The product should be kept in a cool and well ventilated place, protected from heat and direct sunlight. Contents must be kept tightly closed.

Cleaning of Tools:

All tools should be cleaned with water.

Packing:

Available in 1Usg. and 5 Usg. Pail

Physiological Hazards:



See Safety Indication Sheet.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

