



MULTI ETCH SOLUTION

General Description:

An acidic medium with supporting additives especially formulated to cleanse the surfaces from dirt, oil, grease and other contaminants. It is formulated to remove calcareous residues and also serves as a neutralizer to cement concrete.

Major Uses:

For concrete, tiles and the likes.

Characteristics and Physical Properties:

Appearance	Colorless Liquid
Odor	Acidic
Sp. Weight	1.2
Flash Point	Not Flammable
Storage Life	One (1) year
Coverage	12- 20 m ² ./lit.

Method of Application:

Apply by roller or brush to a new and old concrete and keep it for an hour or two. Rinse with clean water and let it dry prior to the application of sealer or primer.

Storage:

Keep material in a cool place below 25°C. Keep the container tightly closed. Shelf life of 12 months minimum.

Cleaning of Tools:

All tools should be cleaned with water as soon as possible.

Packing:

Available in 4 lit (Plastic Usg.) and 20 lit (Plastic Pail)

Physiological Hazards:

MULTI ETCH SOLUTION contains strong acids and it is irritant to skin. It is recommended to wear protective rubber gloves and safety tools when application and avoid contact to your skin and eyes. If incident occurs, wash fresh water and seek for medical assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

