



PUTTY FILLER

General Description:

PUTTY FILLER is based on acrylic resin, nitrocellulose and natural wood fiber, it is developed to patch – up uneven surface of the wood and to fill holes and cracks.

Major Uses:

PUTTY FILLER can be applied over natural and synthetic wood. It is recommended for interior and exterior application.

Characteristics and Physical Properties:

Specific Weight	1 kg/L
Total Solids	50-55%
Flash point	20°C

Colors Available:

- Natural
- Teak
- Light Oak
- Dark Oak
- Mahogany
- Walnut

Method of Application:

- The surface must be primed and should be clean and free from any loose particles.
- Fill the holes and cracks by scraper leave “HEAD’ to allow slight shrinkage.

- If the previous material is dry, treat the uneven surface with PUTTY FILLER.
- PUTTY FILLER should be coated with NC, PU or Acrylic topcoats.

Storage:

PUTTY FILLER should be kept in a cool area below 25°C. Keep in tightly closed container.

Cleaning of Tools:

All tools should be cleaned with Wash Thinner or NC Thinner # 115 as soon as possible.

Packing:

Available in 500 ml., 1 liter

Physiological Hazards:

PUTTY FILLER does not contain dangerous solvents, nevertheless, good ventilation in working rooms is recommended as well as the use of safety tools and equipment. PUTTY FILLER is flammable and harmful if swallowed. If contact with eyes or skin occurs, wash well with fresh water and seek immediate medical advise..

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

