



STAIN - AYD

General Description:

STAIN – AYD is a nitrocellulose based material blend with slow drying organic solvents not interfering with concentrated dyestuff and pigmented paste. It is recommended to use as a carrier for stain in a reverse roller application.

Characteristics and Physical properties:

Appearance	Visual	Clear
Specific Gravity	ASTM D 1475	0.875 kg/li.
Weight solids		16%
Colour (Saybolt)	ASTM D 1209	+30
Boiling Point	ASTM D 850	100°C
Copper corrosion	ASTM D 849	none
Acidity	ASTM D 1613	< 0.03 %
Non-aromatics		40%
Flash point	IP 170	18°C

Application method:

Mix the required dyestuff or pigment paste to STAIN – AYD and stir thoroughly until homogenous solution has been achieved. Colour strength will be based on the percentage addition of stain. No dilution is required.

Storage:

Keep the container tightly closed. Shelf life is unlimited in close container. Keep away from direct sunlight and other sources of heat or ignition; do not smoke in storage areas.

Packing:

Available in USG, 20 liter Pail

Physiological Hazards:

STAIN - AYD contains highly flammable solvents. Always use protective gloves and eye goggles when handling this product. It is highly recommended to provide proper ventilation on working area. If contact with skin or splash in eyes, wash with fresh water and seek medical assistance.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

