



STEELCOTE WHITE

General Description:

STEELCOTE WHITE is a pigmented paint based on polyester and amino resin. It provides fast curing, excellent adhesion, scratch and abrasion resistance, staining resistance, very good chemical and mechanical property. Due to high quality materials, it gives hard and hot stacking resistance.

Major Uses:

The product is recommended as a basecoat for tin can coating suitable for body can jobs.

Characteristics and Physical Properties:

Binder	Polyester
Appearance	Gloss
Colour	White
Specific gravity	1.3 +/- 0.05 kg/L
Viscosity FC #4 25°C	150"
Solid content	61%
Flash point	26°C
Coating rate	12.5 g/m ²
Baking cycle	170-190°C (10~12' peak temp.)
Application method	Roller Coater
Dilution	Thinner # 355

Surface Preparation:

- Substrate should be dry and free from contaminant such as oil, dust and other contaminants.
- The baking schedule and application properties are suggested recommendations and may require to be change suitable to the conditions and efficiency of the equipment.

Storage:

Store in the dark, cool and dry places under normal temperature and humidity. Shelf life of 6 months at 30°C room temperature.

Packing:

Available in 20 lit. pail

Precautions:

STEELCOTE WHITE contains no hazardous solvents, nevertheless use protective gloves and eye goggles when handling this product. It is recommended to provide proper ventilation on working area. If contact with skin or splash in eyes, wash with fresh water and seek medical advise.

The above information is given to the best of our knowledge based on laboratory test and practical experience. However, as the paint is often used under condition beyond our control, we cannot guarantee anything but the quality of the paint itself. We reserve the right to change the given data without prior notice.

MAS PAINTS & CHEMICAL INDUSTRY

P.O. BOX NO: 23085, SAJJAH INDUSTRIAL AREA, SHARJAH, U.A.E

TEL NO: 009716 5311777; FAX: 009716 5311330

Website : <http://www.mas-paints.com>

Email: masuae@emirates.net.ae

